



NT-1200-4K HDMI/USB 3.0 4K UHD Video Camera

NT-1200-4K camera Support HDMI and USB 3.0 ultra-high speed interface, can transfer uncompressed original video. USB 3.0, HDMI, 3G-SDI and LAN can output at the same time.

The H.264/H.265 encoding support conference video camera enabling 4K UHD 60fps video stream with ultra-low bandwidth.



Advantages:

- 1/2.5", CMOS, Max Effective Pixel: 8.51 M
- Smart & Solid design
- Fast and accurate focus performance
- USB Video UVC 1.1~1.5
- Support H.264, H.265 and MJPEG video compression
- USB3.0/ HDMI/ LAN/3G-SDI high speed output
- 3.5mm Audio Interface, Line In
- TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc..

Features:

- Zoom: 12x Optical and 16x Digital Zoom
- 4K@60fps high resolution
- 72.5° field of view
- Effective RS232/485 serial control
- Advanced 2D/3D DNR
- Automatic image flip function
- VISCA, PELCO-D and PELCO-P protocol control

Input/Output Interface:



For more detail, Please Contact
info@confEye.in





NT-1200-4K

HDMI/USB 3.0 4K UHD Video Camera

Technical Specifications | Datasheet

Image Sensor Type : 1/2.5 inch high quality 8.51 MP UHD CMOS Sensor

Video Format : 4K@60fps, 4K@30fps, 1080P@60fps, 1080P@30fps, 720P@60fps,

Video Output : USB 3.0, HDMI, LAN, 3G-SDI

Video Compression : H.264, H.265 and MJPEG

Audio Input : A- IN; Double track 3.5mm liner input

Audio Compression : AAC 96Kbps, 128Kbps, 256Kbps

Network Interface : RJ45: 10M/100M Ethernet Interface

Network Protocol : TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.

Zoom : 12x Optical and 16x Digital Zoom

View Angle(H) : 8.2° ~ 72.5

View Angle(V) : 4.5° ~ 42.7

Pan Rotation Angle : -170° ~ +170°

Tilt Rotation Angle : -30° ~ +30°

Pan Speed : 1.7° ~ 76° /s

Tilt Speed : 0.5° ~ 15° /s

Preset : 255 (10 by remote controller)

Control Port : RS232/ RS485/ LAN

PTZ Control Protocol : VISCA/ PELCO-D/ PELCO-P

POE : Support

Power : DC 12V Power Supply

Focal Length : f=4.4 ~ 52.8mm F1.8– F2.6

Minimum Lux : 0.5 lux (F1.8, AGC ON)

S/N Ratio : ≥55 dB

White Balance : Auto / Manual and other

Focus : Auto / Manual

Shutter : 1/30s ~ 1/10000s

H & V Flip : Support

BLC : Support

DNR : 3D DNR

Dimension (L x W x H) : 169mm x 142mm x 164 mm

Weight : 1.35Kg

* Detail specification for tender is also available.

Order Model No.:

Model No.	Max Resolution	Zoom Optical	Video Output	Color
NT-1200-4K	4K60	12X	USB3.0/HDMI/LAN/SDI	Silver/Black

ConfEye

Add.: B1, 19A, Block B1, Block E, Mohan Cooperative Industrial Estate, New Delhi - 110044.

URL : www.confEye.in, E-mail : info@confEye.in

Toll Free - 1800 5723 308